


5G Beamforming with Versal AI Core Series

- > 2X TMACs/watt¹
- > Support for adaptable O-RAN O-DU and O-RU functional partitioning
- > Adaptable beamforming for evolving algorithms

CHALLENGE

5G New Radio (NR) beamforming is the key to enabling a dramatic increase in network capacity. Beamforming technology, however, requires significant compute density and advanced high-speed connectivity to meet 5G throughput and low-latency requirements. The massive MIMO beamforming algorithms are expected to continue to evolve to increase the utilization of inherent network capacity possible within massive MIMO systems while optimizing fronthaul bandwidth and lowering dissipated power in the radio.

Massive MIMO radio is the leading form factor for 5G commercial deployments, using 32 or 64 antenna elements for beamforming steered towards one or multiple users while using the same spectral resources. For typical radio configuration of a 64 antenna 200MHz system, the beamforming device in the radio needs to perform over 1.5 tera multiply and add (TMAC) operations per second for downlink. Additional compute is needed to perform beamforming in the uplink direction, all while meeting stringent thermal and system footprint constraints.



SOLUTION: VERSAL AI CORE ACAP FOR BEAMFORMING

The Versal[®] AI Core adaptive compute acceleration platform (ACAP) is a highly integrated, multicore, heterogeneous platform that delivers exceptional compute density at low power consumption to perform the real-time, low-latency signal processing demanded by beamforming algorithms in massive MIMO radios. Central to the platform are the AI Engines—a tiled array of C-programmable vector processors with flexible interconnect and distributed memory—ideal for implementing beamforming algorithms that can easily be reprogrammed after deployment.

AI Engines for Performance/Watt

AI Engines provide system-level compute far beyond that of traditional FPGA-based multipliers and DSP blocks, enabling 2X TMACs/watt¹, allowing more programmable logic resources to be used for additional functionality.

Adaptable O-RAN

By using Versal AI Core ACAPs in conjunction with other Xilinx adaptable solutions, network suppliers and OEMs can split baseband processing across distributed units (DU) and radio units (RU) to realize fully adaptable networks.

Adaptable Beamforming

With 5G specifications in flux and beamforming techniques evolving, Versal AI Core ACAPs offer adaptive compute for different algorithm implementations to address a wide range of processing performance and compute precision.

2.14X Performance/Watt¹




¹: Versal AI Core VC1902 ACAP vs. Intel Agilex AGF027 FPGA

VERSAL ACAP IMPLEMENTATION

64TRX 200MHz+ Massive MIMO Beamformer Device

An ACAP implementation provides software programmability for C/C++ developers, hardware adaptability to evolve with beamforming algorithms, and hard IP integration for the on- and off-chip performance/watt and low latency required for 5G.



PLATFORM HIGHLIGHTS


AI Engines	<ul style="list-style-type: none"> > Tiled array of vector processors capable of fixed- and floating-point signal processing and massive parallelism > Perform on-the-fly calculation of phase and gain coefficients for beamforming and Low-PHY acceleration > C/C++ programmable with 1GHz performance
Adaptable Engines	<ul style="list-style-type: none"> > Manage ingress and egress data movement, dynamically controlling accelerators based on radio configuration > Fine grained memory hierarchy to optimize accelerator performance > Fronthaul interface logic—including eCPRI & 1588-PTP packet filter & framer/de-framer, xRAN pre-processing, and more
Scalar Engines	<ul style="list-style-type: none"> > Manage initial system configuration and run-time control > Perform system operation and maintenance (OA&M), S-Plane sync, and M-Plane processing > Run beamforming application software
Programmable Network on Chip	<ul style="list-style-type: none"> > Seamlessly integrates all engines and key interfaces > Simplifies kernel and IP placement, reducing soft logic needed for connectivity > Streamlines programming experience for software and hardware developers
Integrated Shell	<ul style="list-style-type: none"> > Comprises hardened interface (PCIe® w/DMA, DDR4 controllers) and programmable network on chip (NoC) > Ensures streamlined device bring-up and connectivity to off-chip interfaces—making the platform available at boot > Delivers pre-engineered timing closure and logic resource savings
Multirate 100G Ethernet	<ul style="list-style-type: none"> > Enables 10G/25G/50G eCPRI over Ethernet > Optional built-in RS-FEC / FEC and IEEE Std 1588 hardware timestamping

BENCHMARK

Shown below is a comparison of projected results for a 7nm production Versal VC1902 device vs. a 10nm Intel Agilex FPGA. Xilinx Versal AI Engine technology increases desired compute density while reducing power in contrast to an Agilex AGF027 based on traditional FPGA fabric, multipliers, memory, and soft interconnect.

64TRX 200MHz+ Massive MIMO Beamformer Device

RELATIVE MACS/WATT



	Intel Agilex AGF027 -3L		Versal AI Core VC1902 -1LL
Peak Performance	3.3 Complex MACs	▶ 1.5X ▶	4.9 Complex MACs
Effective TMACs ¹	0.6 Complex MACs	▶ 2X ▶	1.2 Complex MACs
Data Scheduling & Data Management	85k ALMs	▶ Hard IP ▶	No LUTs required ²
Logic for Memory Subsystem	50k ALMs	▶ Hard IP ▶	No LUTs required ³
Performance/Watt	1X Complex MACs/Watt⁴		2.14X Complex MACs/Watt⁵

- 1: Assumes 75% DSP utilization for 17,056 Intel Agilex FPGA 18x19 multipliers and 300 of 400 available Versal ACAP AI Engines
- 2: Versal ACAP AI Engines and AI Engine Interconnect provide data movement for compute
- 3: Versal ACAP hardened memory subsystem comprises network on chip and DDR controllers – no programmable logic required
- 4: Based on Quartus Power & Thermal Calculator 2021.2, assumes SmartVID and claimed static power savings
- 5: Based on Xilinx Power Estimator (XPE) available at <https://www.xilinx.com/products/technology/power/xpe.html>

TAKE THE NEXT STEP

- > To learn more about beamforming with AI Engines, read the [application note](#) or watch the [video](#)
- > To try the above benchmark yourself, visit www.xilinx.com/versal-performance-elevated
- > For more information on the Versal AI Core series, visit www.xilinx.com/versal-ai-core
- > To contact your local Xilinx sales representative, visit [Contact Sales](#)

Versal AI Core ACAP VCK190
Evaluation Kit
www.xilinx.com/vck190



Corporate Headquarters
Xilinx, Inc.
2100 Logic Drive
San Jose, CA 95124
USA
Tel: 408-559-7778
www.xilinx.com

Xilinx Europe
Xilinx Europe
Bianconi Avenue
Citywest Business Campus
Saggart, County Dublin
Ireland
Tel: +353-1-464-0311
www.xilinx.com

Japan
Xilinx K.K.
Art Village Osaki Central Tower 4F
1-2-2 Osaki, Shinagawa-ku
Tokyo 141-0032 Japan
Tel: +81-3-6744-7777
japan.xilinx.com

Asia Pacific Pte. Ltd.
Xilinx, Asia Pacific
5 Changi Business Park
Singapore 486040
Tel: +65-6407-3000
www.xilinx.com

India
Xilinx India Technology Services Pvt. Ltd.
Block A, B, C, 8th & 13th floors,
Meenakshi Tech Park, Survey No. 39
Gachibowli(V), Seri Lingampally (M),
Hyderabad -500 084
Tel: +91-40-6721-4747
www.xilinx.com

